

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>C09J 7/02, B65H 35/00, B65D 83/08</b>	<b>A1</b>	(11) International Publication Number: <b>WO 00/15729</b> (43) International Publication Date: <b>23 March 2000 (23.03.00)</b>
(21) International Application Number: <b>PCT/US99/21402</b> (22) International Filing Date: <b>16 September 1999 (16.09.99)</b>  (30) Priority Data: <b>09/154,005 16 September 1998 (16.09.98) US</b>  (71) Applicant: <b>LINEAR PRODUCTS INC. [US/US]; 417 N.W. 136th Street, Vancouver, WA 98685 (US).</b>  (72) Inventors: <b>FOUBERT, Roland, A.; 417 N.W. 136th Street, Vancouver, WA 98685 (US). DRAPALA, Wieslaw, A.; 417 N.W. 136th Street, Vancouver, WA 98685 (US). WILLIAMS, Kimberly, J.; 417 N.W. 136th Street, Vancouver, WA 98685 (US). CATTERLIN, Richard, G.; 417 N.W. 136th Street, Vancouver, WA 98685 (US).</b>  (74) Agents: <b>QUAN, Nancy, N. et al.; 1200 Willow Lake Boulevard, Box 64683, St. Paul, MN 55164-0683 (US).</b>	(81) Designated States: <b>AU, CA, CN, JP, MX, NZ, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</b>  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(54) Title: <b>FILM TAPE FOR FORMING A CUTTING EDGE ON DISPENSER CARTONS</b>  (57) Abstract  A tape formed of a polymeric material and having a thickness and stiffness suitable as a cutting edge on a dispensing carton for convolutely wound foil, film or paper, the tape includes a coating of adhesive and is applied at a laminating station in the carton manufacturing process and is generally cut with the forming of the carton blanks, and the cut in the tape may be formed with a serrated edge.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## FILM TAPE FOR FORMING A CUTTING EDGE ON DISPENSER CARTONS

### Background of the Invention

### Field of the Invention

5           This invention relates to a novel tape for forming a cutting edge on cartons or boxes for convolutely wound rolls of film, paper or foil products, and in one aspect to a new method for applying a cutting edge in-line with the printing or sheeting station of the carton manufacturing machine. The cutting edge is formed of a polymeric material adhered to the carton for cutting lengths of material from a roll in the carton.

### Description of the Prior Art

10           The prior art is replete with teachings of using a rectangular dispensing carton for a roll of sheet material, which material is intended to be dispensed and severed in the desired length from the carton by the consumer. The cartons generally have a cutter on an edge of the front panel or on the lid to aid in cutting the material. The cutter is formed with a saw-  
15           toothed edge to guide the cut across the width of the sheet material.

          The saw-toothed or serrated cutting edge has been typically formed of a metal (EP 352634 A dated 19900131, US 5,078,311) or from the carton paper or board impregnated with resin (WO 9635574 A2), or by reinforcing a paper carton with plastic or vulcanized  
20           fiber materials with an ultrasonic fusion member (JP 8309890 A dated 19950522). US patent No. 4,405,066 discloses a flip top dispenser carton of the type related to the present invention wherein the invention relates to the flaps forming the ends of the carton. It also teaches that the longitudinally extending free edge of the outer panel is straight and is provided with a plastic reinforcing strip. The patent teaches the combination of a straight  
25           edge 40 and the reinforcing strip 42 provides a rigid cutting surface for tearing heavier rolls of film such as wax paper and aluminum foil. The reinforcing plastic is applied to adjacent blanks which are contiguous, such that a single cut, defining the free edges of both blanks simultaneously forms the side edges of both plastic strips, producing a cutting edge at lower cost than the metal saw-tooth blades.

The present invention differs from the prior art in that the present invention compares a film tape coated with an adhesive for continuous application to a carton fiber board or to the blank to form a resulting reinforced cutting edge on the lid flap or front panel of a carton. The tape is applied to the carton board during the normal box making process. The tape is formed of a polymeric material which is strong enough to serve the numerous cutting operations on the material dispensed from the ultimate carton but not as sharp or likely to cause injury to the consumer as the current methods.

### Summary of the Invention

The present invention provides a new film tape coated with adhesive for application to the carton board of a carton for a convolutely wound roll of sheet material in which the tape serves as the cutting edge on the carton for the material. The tape is formed of a polymeric film material in a continuous strip which is stiff enough, when applied to the free edge of a carton to provide the cutting function. The exposed edge may be a straight or a serrated edge. Further, the tape of the present invention reduces the number of stations used in the carton forming machine to apply the cutting edge. The application of a metal cutting edge requires the application station and a station for riveting or stapling the metal to the blank. The method of the present invention requires a laminating step or station in-line with the printing or sheeting station to apply the tape before the blanks are cut or separated. If the tape is applied to blanks placed in mirror-image to each other, the tape is applied to both blanks simultaneously and the tape is then cut lengthwise to form the cutting edge on each blank and to separate the blanks.

### Brief Description of the Drawing

The present invention will be further described with reference to the accompanying drawing wherein:

Figure 1 is a perspective view of a roll of the tape material of the present invention:

Figure 2 is a schematic view of the application of the tape to a sheet of fiber board moving through the box forming machine;

Figure 3 is a plan schematic view of the tape applied to the fiber board and then cut into mirrored pairs of box blanks with the tape applied and cut on center to separate the box blanks before the folding station;

Figure 4 is a perspective view of a dispenser carton showing the cutting tape applied along the top edge of the front panel forming the cutting edge, and

Figure 5 is a detail view showing the tape applied to two carton blanks and cut to form a saw-tooth or serrated edge.

### Description of the Preferred Embodiment

The present invention provides a polymeric tape for forming the cutting edge on a rectangular dispensing carton or box for polymeric wrapping film, waxed or other paper, or metal wrapping foil.

Referring now to the drawing, the tape 6 comprises a polymeric backing 8 coated with an adhesive 9, preferably a hot melt adhesive. The tape 6 is transversely or convolutely wound to provide a continuous supply of tape to a carton making machine such that it can be applied in-line at a laminating station. The laminating station is in-line with the printing or sheeting station of the carton forming machine.

Figure 2 schematically illustrates the application of the tape 6 to a carton board 20 as it is advanced through the carton manufacturing machine in the machine direction. The tape 6 passes over a feed or idler roller 21 to an applying roller 22 and under a pressure or laminating roller 23. One or both of the rollers 22 and 23 can be heated to apply a tape 6 coated with a hot melt adhesive 9. Beyond the laminating station is the die cutting station 25 which die cuts the carton blanks from the carton board 20 and cuts the tape 6 to length on the blank and down the middle to separate two carton blanks, see Figure 3.

The carton 10 normally includes a front panel 11, a bottom panel 12, a rear panel 14, and a lid 15, which is hingedly joined to the rear panel 14, and a closing flap 16, joined to the free edge of the lid 15, to cover a portion of the front panel 11. Flanges 17 on the ends of the front, bottom and rear panels form the ends 18 of the carton 10, and as illustrated the lid 15 can be formed with a flange 19, which is torn away from the ends of the lid 15 upon opening the carton 10. The carton 10 is rectangular, having a length considerably greater than its width to support a roll of sheet material, i.e., clingfilm, paper

or foil, not shown. Typically a cutter blade is riveted to the upper edge of the front panel 11 or to the free edge of the closing flap 16. In the present invention the cutter bar 30 is formed by the polymeric tape 6 bonded to the upper free edge of the front panel 11. The cutter bar 30 has a straight edge projecting just above but generally parallel with the top edge of the front panel over which the material is drawn and then torn across the cutter edge. The tape forming the cutter bar can also be cut so as to form a saw-toothed or serrated free edge to aid in cutting the sheet material.

As shown in schematic form in Figure 5, the tape is applied to blanks in contiguous manner, but spaced between the adjacent edges formed to support the cutting bar 30. When the tape is applied to the two moving blanks it is registered with the moving blanks and laminated as explained above. The tape is then cut and in this manner it can be cut to project just above the edge of the front panel 11 or the flap 16 on the lid. As illustrated the tape is cut to have a saw-toothed edge. Alternatively, the tape 6 can be formed to be applied to individual blanks and formed with a straight or serrated edge.

In the present invention, the tape 6 comprises a film backing 8 and an adhesive 9. The film backing is formed of polyester, polypropylene, polyethylene or similar polymeric material having sufficient strength to support the cutting function, and preferably polyester. The backing is heat resistant between about 160°F (71°C) and about 350°F (177°C), preferably at least 250°F (125°C). The backing 8 has a thickness between 2 mils (0.05 mm) and 7 mils (0.18 mm), preferably 4 mils (0.1 mm), with a width of 0.25 inch (.60 cm) to 1.25 inches (3.2 cm), and preferably the cutting edge on the carton is 0.25 inch (.60 cm) in width. If the tape is applied to blanks placed in mirror images to each other, a wider tape is preferred, preferably twice as wide as that used as the cutting edge on each blank.

The adhesive 9 exhibits high adhesion characteristics to the film backing and the carton board such that it maintains a good bond under the normal wear and tear exerted on the carton. A preferred adhesive formulation is:

	<u>Wt-%</u>	<u>Material</u>	<u>Available From</u>
	20.0	AC 830	Allied Signal, Inc., Morristown, NJ
30	4.0	Be Square 195	Bareco Products, Rock Hill, SC
	28.0	Unitac R99	Union Camp Corporation, Jacksonville, FL

	12.0	Norsolene A110	Sartomer Company, Exton, PA
	0.50	Lenox 10	Alphachem International Corp., Lake Oswego, Or.
	10.0	AT2820	AT Plastics Edmonton, Alberta Canada
5	25.5	Elvaloy HP771	Dupont, Wilmington, DE

Alternatively, for a properly treated film, the adhesive 9 can be any available hot melt adhesive that exhibits high adhesion characteristics to carton board. When other hot melt adhesives are used, the tape backing is preferably corona treated to improve adhesion  
10 of the adhesive to the backing. Other means of improving the adhesion can also be used, such as treating the backing with adhesion promoters.

Available hot melts for the adhesive 9 can be any typical hot melt adhesive or hot melt pressure-sensitive adhesive such as an ethylene-vinyl acetate copolymer (EVA-based) hot melt adhesive; a metallocene based hot melt pressure-sensitive adhesive such as those  
15 comprising at least one homogeneous linear or substantially linear interpolmer of ethylene and at least one C<sub>3</sub> to C<sub>20</sub> alpha-olefin; EMA-based hot melt and hot melt pressure-sensitive adhesive (ethylene methylacrylate); EnBA-based hot melt adhesive (ethylene n-butyl acrylate); hot melt adhesives based on polyethylene and polypropylene homopolymers, copolymers and interpolymers, or rubbery block copolymer hot melt adhesives. In general,  
20 if EVA-based hot melt adhesives are used, they typically comprise about 15% to about 40% EVA, about 10% to about 35% wax, about 20% to about 40% resin, and about 0.2% to about 0.4% anti-oxidant. These adhesives exhibit high adhesion characteristics to the carton board, and the backings 8 can be treated to improve its adhesion to the adhesives.

It is surprising that even though the tape is relatively thin, it performs as a very  
25 good cutting edge, especially when the tape projects just above the panel.

The tape is used in the carton manufacturing process to be applied to the carton material as the same moves through the carton forming machine in the machine direction. The tape is applied at one station in the process to laminate the adhesive coated surface against the carton board and is then cut to form a cutting edge along the edge of the front  
30 panel or the closing flap on the lid. The tape may be cut to form a straight edge or a serrated edge. Alternatively, the tape is cut to form serrations along one edge during the



manufacture of the rolls of tape. The application of the cutting edge tape takes place at one station and after a registered amount of tape is dispensed, registered and laminated to the carton board adjacent the edge of the carton board forming the free upper edge of the front panel, it is cut from the roll.

5 For the embodiment where the cutting edge extends beyond the edge of the front panel of the carton, whether the edge is straight or serrated, the adhesive is coated on the backing such that the exposed edge is free of adhesive, if the adhesive used is pressure-sensitive. If the adhesive becomes cured after application, then the adhesive can be present on the exposed edge as well.

10 The adhesive thickness ranges from a coating weight of about 3 to about 10 g/sq ft ( $\text{g}/929 \text{ cm}^2$ ), preferably of about 3.3 to about 4 g/sq ft. ( $\text{g}/929 \text{ cm}^2$ ).

An alternative way of using the tape to form a cutting mechanism is to apply the tape to carton board that will be cut into a single rectangular shape that can act as an insert into the box that holds the roll of film to be cut. A wide tape can be used so that  
15 the inserts can be made in a mirror image and the tape can be cut down the center with  $\frac{1}{2}$  ending up on each insert. The top edge of the insert can be either a straight edge or a serrated pattern. Alternatively the tape can be applied along the edge of the carton board so that it extends above the edge of the carton board when the insert is cut out, providing a sharper surface against which to tear the film to be cut.

20 Inserts produced in the method described above can be inserted as cutting mechanisms into dispensing cartons made of carton board or larger institutional dispensing boxes made of corrugated.

When the tape is used in a fashion such that it extends above the edge of the carton board, the tape can be manufactured so that only  $\frac{1}{2}$  of the surface is coated with  
25 adhesive. This would assure that the surface of tape that extends above the carton board is free of adhesive on both sides.

Having disclosed the present invention and equivalents thereof, it is to be understood that other changes can be made therein without departing from the spirit and scope of the invention claimed in the appended claims.



**Claims**


1. An adhesive tape for use as a cutter bar for dispensing cartons, said adhesive tape comprising:
  - 5 a) a backing of between about 2 mils (0.05 mm) to about 7 mils (0.18 mm) in thickness comprised of a polymeric film material selected from the group consisting of polyester, polypropylene and polyethylene, and
  - b) said backing having opposite edges, and opposite sides, one of said sides being coated with an adhesive having high adhesion to a fiber board for  
10 forming dispensing cartons.
2. The tape of Claim 1 wherein one edge of the tape is formed with a saw-toothed edge.
- 15 3. The dispensing carton of Claim 1 wherein said cutting edge is a straight edge.
4. The tape of Claim 1 wherein said adhesive is selected from the group consisting of heat activated hot melt adhesives and hot melt pressure sensitive adhesives.
- 20 5. The tape of Claim 4 wherein said adhesive is an EVA based hot melt adhesive.
6. The tape of Claim 5 wherein said backing is corona treated.
7. A method of forming a cutting edge on a dispensing carton for film, foil or paper  
25 comprising the steps of:
  - a) forming a tape having a polymeric backing coated with an adhesive on one side,
  - b) supplying a roll of said tape to the application station in a box forming machine,
  - 30 c) applying the tape to the carton board in the box forming machine and laminating the same, and



- d) cutting the carton board into carton blanks and the tape lengthwise to form a cutting edge on each blank.
8. The method of Claim 7 wherein the method includes the step of die cutting the carton board and the tape to form a serrated edge in the tape adhered to the carton board.
9. The method of Claim 7 wherein the method includes the step of cutting the tape backing to form a serrated edge along an edge of the tape.
10. The method of Claim 7 wherein the tape comprises a backing formed of a polymeric material selected from the group consisting of polyester, polyethylene and polypropylene.
11. The method according to Claim 10 wherein the adhesive comprises an EVA hot melt adhesive.
12. The tape of Claim 1 wherein said backing is heat resistant between about 160°F (71°C) and about 350°F (177°C).
13. The method according to Claim 11 wherein said backing is corona treated.
14. A dispensing carton for use in dispensing foil, paper and film comprising:
- a) a front panel, a bottom panel, a rear panel, each having panels at opposite ends to form the ends of the carton;
- b) a lid connected to the rear panel and a flange joined to the lid to overlap said front panel; and
- c) a cutting edge formed on one of said front panel and said flange joined to said lid for severing lengths of material dispensed from said carton, said cutting edge formed of a polymeric material selected from the group comprising polyester, polypropylene and polyethylene and having a

thickness between 2 mils (.05 mm) and 7 mils (.18 mm) and adhered to said one of said panel and flange by adhesive.

15. The dispensing carton of Claim 14 wherein the adhesive comprises an EVA hot melt adhesive.
16. The dispensing carton of Claim 14 wherein the polymeric material backing is heat resistant between about 160°F (71°C) and about 350°F (177°C).
17. The dispensing carton of Claim 14 wherein said cutting edge has a serrated edge .
18. The dispensing carton of Claim 14 wherein the cutting edge projects above the edge of the front panel.
19. The dispensing carton of Claim 14 wherein said backing is corona treated.
20. The dispensing carton of Claim 14 wherein said cutting edge is a straight edge.







# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 99/21402

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 C09J7/02 B65H35/00 B65D83/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 C09J B65H B65D B26F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	EP 0 776 848 A (MINNESOTA MINING & MFG) 4 June 1997 (1997-06-04) page 2, line 37 - line 57 page 3, line 31 - line 48 page 4, line 57 - page 5, line 1 page 5, line 14 - line 17 page 6, line 15 - line 17 figures 1-3, 7-10 ---	1-4, 14, 16-18, 20 7
X A	US 3 886 033 A (MACDONALD WILLIAM ET AL) 27 May 1975 (1975-05-27) abstract figures 7-9 column 2, line 4 - line 29 column 3, line 21 - line 27 column 3, line 44 - column 4, line 34 --- -/--	1-5 7-18, 20

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"A" document member of the same patent family

Date of the actual completion of the international search

10 January 2000

Date of mailing of the international search report

20/01/2000

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Schlicke, B



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 99/21402

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 29 30 725 A (OSTHUSHENRICH KG) 19 February 1981 (1981-02-19) claims 1-3,5 ----	1-20
A	EP 0 603 398 A (HONSHU PAPER CO LTD ; TOYO FIBRE CO LTD (JP)) 29 June 1994 (1994-06-29) page 5, line 16 - line 28 examples 3,4 -----	1-20

# INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 99/21402

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0776848 A	04-06-1997	CA 2190323 A	30-05-1997
US 3886033 A	27-05-1975	NONE	
DE 2930725 A	19-02-1981	NONE	
EP 0603398 A	29-06-1994	DE 69220373 D	17-07-1997
		DE 69220373 T	20-11-1997
		WO 9304935 A	18-03-1993
		JP 2824901 B	18-11-1998
		JP 8192479 A	30-07-1996
		JP 2606776 B	07-05-1997
		JP 6048428 A	22-02-1994